

## And they're easy to remove without mess ...

1. Plug in the HeatGun and heat it up for five minutes.
2. Carefully place the hot Gun over the Disc to be removed for a few seconds until the disc will move.
3. Slide the wire Disc remover over the disc and, while pinching the wire 'arms' gently pull the Disc away from the surface.
4. Wet a clean rag with mineral spirits and wipe off adhesive residue while it is still warm.
5. Throw away the used Disc when it is cool. Any remaining adhesive cannot be reused. The Disc is made of recyclable material.



## IMPORTANT ELECTRICAL SAFETY INSTRUCTIONS

### Please read carefully

Warning: When using electrical tools, basic safety precautions should always be followed to reduce the risk of fire, electrical shock and personal injury.

1. Do not touch the heating element or the melted glue on the disc.
2. Avoid dangerous environments. Don't use the tool in damp or wet locations or expose it to rain. Keep work area well lighted. Do not use in the presence of flammable liquids or gases.
3. Guard against electrical shock. Prevent body contact with grounded surfaces.
4. Do not modify the plug in any way.

Duzzit™ is a registered trademark of Interwood Marketing Limited



## HANDY HANGER ALL-SURFACE HANGING SYSTEM



**For Best Results  
Please Read These  
Instructions**

## Directions:

### Step 1

Thoroughly clean and dry the surface. Use available household cleaners that will not leave a 'film', or use rubbing alcohol.

### Step 2


Plug in and preheat the Duzzit HeatGun for five minutes. Carefully place a Disc on the end of the HeatGun and heat for 60 seconds.

### Step 3

Press the Disc onto the surface with the HeatGun for at least 25 seconds.

### Step 4

Remove the HeatGun and wait 24 hours for the adhesive to thoroughly cool, cure and bond to the surface, before hanging anything on the Disc.



### Step 5


Hang a wire directly on the Disc, or slide a Hook over the Disc.

## These surfaces can hold up to FIVE pounds with a Single Disc

- ✓ Ceramic Tile
- ✓ Glass
- ✓ Painted Walls
- ✓ Painted Wood
- ✓ Enameled Appliances
- ✓ Plastic
- ✓ Sheet Rock

## These surfaces can hold up to TEN pounds with a single Disc

- ✓ Brick
- ✓ Formica
- ✓ Prefinished Cabinets
- ✓ Plaster
- ✓ Wood Panelling
- ✓ Concrete
- ✓ Hollow Wood Doors
- ✓ Tub & Shower Enclosures
- ✓ Urethane Coated Stained Wood



## Using Disc Plus Hook

Using a Hook puts more strain on the Disc. We recommend you hang no more than THREE pounds on these surfaces with a Hook.

## More Helpful Tips ...

- Keep the HeatGun plugged in while in use.
- If the item to be hung from the Disc will be pulling away from the wall at an angle instead of hanging straight down, use the hanging capacities recommended for Hooks.
- Be very careful when hanging an object on any painted or finished surface. The weight hanging capacity is limited by the adhesion to the paint, paper or surface finish. We suggest that you do not use the Disc on wallpapered surfaces without testing first.
- For larger or heavy objects use two Discs. When two Discs are used to hang an item, place the Discs side by side to ensure alignment.
- Newly painted or stained surfaces should be allowed to cure for a minimum of 30 days if latex paint, or 60 days if the paint is oil based, before applying Discs.
- Discs and Hooks should not be installed where the temperature is consistently higher than 110 degrees F, or below freezing.
- Please take extra care when hanging unusually heavy or valuable objects. Release them slowly while hanging. The weight bearing ability of the Duzzit System depends on the strength of the surface treatment and its adhesion to the wall.
- When applying Discs on tile and other smooth surfaces it is extremely important that they are clean, dry and grease-free.